

PureWaterCooler™

by VERTEX

Hot & Cold Countertop water dispenser

Bottle-less water cooler is great for small offices and break rooms. Order optional filter pack or provide your own source of filtered water.

Standard Features

- 2 Temp: Cold: 37-50° F, Adjustable • Hot: 180° F, Autocontrol
- LED indicator for hot and cold water on the front panel
- Individual on/off switches for hot or cold function on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- Convenient, enclosed, no-drip dispensing faucets
- Type 304 stainless steel hot and cold water tanks
- High efficiency sealed compressor cooling system with adjustable cold water thermostat, 37-50°F
- Safety lock for hot water faucet



Executive Gray option



Optional Add-On Filter Pack

Attaches to back of Cooler

- 2 Filtration Options:
 - 2-stage standard filtration takes out sediment, chlorine taste and odor
 - 3-stage adds 50 GPD Reverse Osmosis membrane to remove contaminants
- Adds only 4.5" to cooler depth



Filter Pack installs easily with 4 screws
2-stage, standard filtration shown

Specifications

Shipping Weight: 42 lb.
 Dimension: 13"W x 15"D x 19.5"H
 Cold tank volume 1 gal
 Hot tank volume .5 gal
 Cooling Rate: 1.5 gal/hr 37-50 °F
 Heating Rate: 1.5 gal/hr 180 °F
 Voltage: 115 VAC
 Power Required: 600w, max
 Meets Energy Star Requirements



Filter System Option

Standard Filter **500/FP**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon
 Reverse Osmosis Filter **500/FPR**
 Above 2 stages plus
Stage 3: 50-GPD RO Membrane
 Fully assembled
 - connection hardware included

ORDERING INFORMATION

2-Temp Hot and Cold Dispenser	PWC-500
Add-on filter pack - Standard Filtration	add /FP
Add-on filter pack - 50 GPD Reverse Osmosis membrane	add /FPR
Executive Gray Cabinet	add /EG
Replacement Filters	
Sediment	IFA-4035
GAC Carbon	IFA-4034
RO membrane, 50 GPD	MA-4203

Authorized Dealer