

PureWaterCooler™

by VERTEX

3-Temp Countertop water dispenser

Largest Capacity countertop dispenser available provides Hot, Room and Cold water without the hassles of 5-gallon bottles. Order optional filter pack or provide your own source of filtered water.

Standard Features

- Hot, Room and Cold Temperatures from a single source
- Separate hot/cold power switch front panel
- Reboil raises water 15° F over normal hot water temp.
- Automatic heating control at 180 °F with over-temperature shut-off
- Sealed compressor cooling with adjustable thermostat, 37-50°F
- Stainless steel hot and cold water tanks
- Automatic float valve with solenoid feedwater shut-off
- Water level indicator built-in
- Safety lock for hot water faucet

Optional Add-On Filter Pack

Attaches to back of Cooler

- **2 Filtration Options:**
 - 2-stage **standard filtration** takes out sediment, chlorine taste and odor
 - 3-stage **adds 50 GPD Reverse Osmosis membrane** to remove contaminants
- **Adds only 4.5" to cooler depth**



Executive Gray option



Filter Pack installs easily with 4 screws
2-stage, standard filtration shown

Specifications

Shipping Weight: 44 lb.
Dimension: 16"W x 13"D x 20"H
Cold tank volume .5 gal
Hot tank volume .5 gal
Room temp. tank volume 2.2 gal
Cooling Rate: 1.5 gal/hr 37-50 °F
Heating Rate: 1.5 gal/hr 180 °F
Voltage: 115 VAC
Power Required: 600w, max



Filter System Option

Standard Filter **600/FP**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon
 Reverse Osmosis Filter **600/FPR**
 Above 2 stages plus
Stage 3: 50-GPD RO Membrane
 Fully assembled
 - connection hardware included
 Meets Energy Star Requirements

ORDERING INFORMATION

3-Temp Dispenser	PWC-600
Add-on filter pack - Standard Filtration	add /FP
Add-on filter pack - 50 GPD Reverse Osmosis membrane	add /FPR
Executive Gray Cabinet	add /EG
Replacement Filters	
Sediment	IFA-4035
GAC Carbon	IFA-4034
RO membrane, 50 GPD	MA-4203

Authorized Dealer